

Main Technical Specifications

型号 Model		GR100	GR135	GR165	GR180	GR200	GR215	GR230	
发动机 Engine	厂家	东风康明斯	东风康明斯	东风康明斯/上柴	进口康明斯/上柴	上柴	进口康明斯/东风康明斯	东风康明斯	
	发动机型号 Engine model	4BTA3.9	6BT5.9	6BTA5.9/SC8D170G2B1	CTAA8.3/SC8D190G2B1	SC8D200G2B1	CTAA8.3/6CTA8.3	6CTA8.3- C230- II	
	额定功率/转速 Rated power/speed	kw/rpm	74/2200	97/2200	125/2200	138/2200 140/2300	147/2300	153/2200 160/2200	172/2200
性能参数 Performance specification	前进速度 Traveling speed forward	km/h	5,8,11,17,24,38	5,8,13,20,30,42	5,8,11,19,23,38	5,8,11,19,23,38	5,8,11,19,23,38	5,8,11,19,23,38	5,8,11,19,23,38
	后退速度 Traveling speed reverse	km/h	5,11,24	5,13,30	5,11,23	5,11,23	5,11,23	5,11,23	5,11,23
	牵引力(f=0.8) Tractive force	kN	41.6	61.3	82	84	87	90	90
	最大爬坡能力 Max.gradeability	%	30	30	30	30	30	30	30
工作参数 Operating specification	最小转弯半径 Min.turning radius using articulation	m	5.9	6.6	7.3	7.3	7.3	7.3	7.3
	最大提升高度 Maximum lift above ground	mm	300	410	450	450	450	450	450
	最大铲土深度 Maximum depth of cutting	mm	350	515	500	500	500	500	500
铲刀 Blade	最大侧倾角度 Maximum blade position angle	°	45	90	90	90	90	90	90
	切削角 Blade cutting angle	°	28~70	54~90	28~70	28~70	28~70	28~70	28~70
	回转角 Circle reversing rotation	°	120	360	360	360	360	360	360
	长度x弦高 Moloboard width x height	mm	3048x450	3660 × 610	3660 × 610/3965 × 610	3660 × 610/3965 × 610	4270x610	3965 × 610/4270 × 610	4270x610
	整机外形尺寸 Dimension (LxWxH)	mm	6880x2375x3150	8015x2380x3050	8900x2625x3470	8900x2625x3470	8932x2625x3470	8970x2625x3470	8970x2625x3470
	整机质量 (标配) Operating weight(Standard)	kg	7000	11200	15000	15400	16000	16500	16500